

# Copper Cable Lugs

## Two Hole & Blank Hole

### Type ACUS2H & ACUSBL

Material : E-Copper  
 Finish : Electro Tinned  
 Features : With inspection hole (Also available without inspection hole)

#### Standard Palm

CABLE mm <sup>2</sup>	ØE	PART No.	DIMENSIONS IN mm						
			A	C	D	G	G+H	B	L
16	10.5	ACUS2H1610	5.4	7.1	15	40	64	15	84
25	10.5	ACUS2H2510	6.8	8.8	18	40	64	15	87
35	10.5	ACUS2H3510	8.2	10.6	18	40	66	17	90
50	13	ACUS2H5012	9.5	12.4	22.5	40	66	27.5	102
70	13	ACUS2H7012	11.1	14.3	24	40	67	30	107
95	13	ACUS2H9512	13.5	17.4	26	40	67	33	111
120	13	ACUS2H12012	15	19.4	28	40	70	36	118
150	13	ACUS2H15012	16.5	21.2	31	40	72	44	130
185	13	ACUS2H18512	18.5	23.5	35	40	76	55	149
240	13	ACUS2H24012	21	26.5	38	40	78	55	150
300	13	ACUS2H30012	23.5	30	42	40	84	55	160
400	13	ACUS2H40012	27.5	35.5	52	40	80	62	165
500	13	ACUS2H50012	30	37	55	40	80	62	165
630	13	ACUS2H63012	34	41	60	40	82	70	180

Dimension G as and other stud hole sizes available as per requirements.

#### Blank Palm

CABLE mm <sup>2</sup>	ØE	PART No.	DIMENSIONS IN mm					
			A	C	D	P	B	L
50	BLANK	ACUSBL50MBL	9.5	12.7	22	71	22	99
70	BLANK	ACUSBL70MBL	11.1	14.3	28	88	25	120
95	BLANK	ACUSBL95MBL	13.5	17.5	26	74	25	106
120	BLANK	ACUSBL120MBL	15.5	20.6	29	74	32	113
150	BLANK	ACUSBL150MBL	16.3	22.2	33	82	32	122
185	BLANK	ACUSBL185MBL	18.3	24.3	35	82	32	122
240	BLANK	ACUSBL240MBL	21.2	28.6	40	86	42	145
300	BLANK	ACUSBL300MBL	23.8	31.9	45	94	47	160
400	BLANK	ACUSBL400MBL	27.5	35.5	49	94	50	164
500	BLANK	ACUSBL500MBL	30	38	55	94	50	164
630	BLANK	ACUSBL630MBL	34.5	44	63	98	55	173

