

Industrial Brass Cable Gland Type : A2

For Unarmoured Cables

Suitable for indoor & outdoor conditions. For all of unarmoured cables, plastic or rubber sheathed cables. Provides seal on outer sheath.
TESTED AS PER IEC 62444:2010

TECHNICAL DATA

Type	: A2
Design Specification	: BS 6121:Part 1:1989, EN 50262:1999, IEC 62444
Gland Material	: Brass
Seal Material	: Thermoplastic Elastomer
Cable Type	: Unarmoured
Sealing Technique	: Compression Seal
Sealing Area	: Cable Outer Sheath
Finish	: Natural Brass / Nickel Plated



Part No.	Gland size	Entry thread (C)	Min.thread length (D)	Overall cable dia. (A) min	Overall cable dia. (A) max	Across corners (D) max	Pack quantity
AA2-16S	16S	M16	10	3.5	7	23	2
AA2-16	16	M16	10	4.5	8.5	23	2
AA2-20S	20S	M20	10	8	11.5	25	2
AA2-20	20	M20	10	11	14	25	2
AA2-25S	25S	M25	10	14	17.5	34	2
AA2-25	25	M25	10	17.5	20.4	34	2
AA2-32	32	M32	10	20	26	40	2
AA2-40S	40S	M40	15	26	30	52	1
AA2-40	40	M40	15	30	33	52	1
AA2-50S	50S	M50	15	33	38	61	1
AA2-50	50	M50	15	38	44	62	1
AA2-63S	63S	M63	15	44	50.5	77.5	1
AA2-63	63	M63	15	50	56	77.5	1
AA2-75S	75S	M75	15	56.5	62	89	1
AA2-75	75	M75	15	62	68	89	1
AA2-90S	90S	M90	15	69	75	112	1
AA2-90	90	M90	15	72	78	112	1