

# Industrial Brass Cable Gland Type : PG

## For Cables

Our PG brass dome top glands offer high quality and reliability. Suitable for use in plants and automation technologies where exceptional and safe function is required. Glands with excellent strain relief.



### TECHNICAL DATA

Type	: PG
Specification	: BS 6121:Part 1:1989
Gland Material	: Brass
Armour Clamping	: Clamping Insert
Clamping Insert Material	: Polyamide 6
Sealing Ring Material	: Neoprene
Cable Type	: Single Wire Armour (SWA)
Finish	: Nickel Plated

Part No.	Thread size	TD (hole size mm)	TL (length of thread)	Cable range Min-Max Ø (mm)	Pack qty
APG7	PG7	12.5	6	3.0 - 6.5	1
APG9	PG9	15.2	6	4.0 - 8.0	1
APG11	PG11	18.6	6	5.0 - 10.0	1
APG13.5	PG13.5	20.4	6.5	6.0 - 12.0	1
APG16	PG16	22.5	6.5	10.0 - 14.0	1
APG21	PG21	28.3	7.2	13.0 - 18.0	1
APG29	PG29	37	8	18.0 - 25.0	1
APG36	PG36	47	9	22.0 - 32.0	1
APG42	PG42	54	12	30.0 - 38.0	1
APG48	PG48	59.3	14	34.0 - 44.0	1